

## Airborne Instrumentation Telemetry Antenna



### Features

- Aerodynamic design
- Small compact common footprint
- Built to withstand extreme shock and vibration

### Description

These antennas have been in use for over 20 years in airborne applications. They are well suited to high dynamic airborne environments. These antennas can also be used in ground applications such as racecars and other vehicles.

### Common Specifications

**Connector:** TNC (50Ω) optional

**Footprint:** 6.00" X 0.46"

**VSWR:** 1.5:1 (max)

**Impedance:** 50 ohms

**Temperature:** -50°C to 215°C, 315°C transient

**Polarization:** Linear

**Radiation Pattern:** Hemispherical

**Required mounting screws:** Two M5 X 0.8 THD X 7.5 mm

	<b>FREQUENCY BAND</b>
	P-Band
Frequency Range	215 - 260 MHz
Style	Straight
Height	0.94"
Weight	3.0 oz max
Model	ANT-00810T-6
TTC #	191020002-006

Revision 06/03/2016

### ANT-00810T-6 Datasheet

©2016 Teletronics - A Curtiss-Wright Company

Specifications subject to change without notice.

Approved for Public Release 16-S-2132

Teletronics - A Curtiss-Wright Company

15 Terry Drive, Newtown, PA 18940

phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

**www.ttcdas.com**



Management System  
AS9100C  
ISO 9001:2008