


8-Channel ARINC-429 Bus Monitor Card



Applications

- Commercial aircraft instrumentation
- Avionics
- Lab test

Features

- 8-channel ARINC-429 bus monitor card
- EDAU-2000 and CDAU-2000 compatible
- Supports up to 256 labels per bus
- Timestamps the receipt of a valid word
 - Supports high, low and micro Timestamp
- Operates in the “listen mode”
- Programmable “high” or “low” speed (2-channel basis)
- Programmable data storage based on data labels and SDI bits
- Microsoft Windows application software included

Description

The BIM-429-4 is an 8-channel ARINC-429 bus monitor card for use in TTC’s EDAU-20XX or CDAU-20XX series products. The card receives data from up to eight (8) standard avionics ARINC-429 serial digital data buses. The incoming data rate is programmable on a 2-channel basis at either 12.5 kHz (lo speed) or 100 kHz (hi speed). High time, low time, and micro timestamping are available on a per-word basis. All incoming ARINC-429 data is stored on the card and is programmable by the user for insertion in the PCM output format as “Class I PCM” (standard fixed-position).

Revision 05/12/2015

BIM-429-4 Datasheet

©2015 Teletronics - A Curtiss-Wright Company
Specifications subject to change without notice.

Approved for Public Release 15-S-2254

Teletronics - A Curtiss-Wright Company

15 Terry Drive, Newtown, PA 18940

phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com



CAIS
Compatible



Management
System
AS9100C
ISO 9001:2008