

2-Channel Optical Fibre Channel Receiver Card



Applications

- High-speed data acquisition systems
- Flight test data recording
- Flight test instrumentation

Features

- For use in TTC'S AIM products
- Two (2) independent optical Fibre Channel receivers (receive only)
- Adheres to ANSI open Fibre Channel standards
- Each channel supports half-duplex operation
- Interfaces provided on single optical D-Subminiature connector
- Interfaces to customized 66Mhz-64bit CompactPCI® bus interface
- Full-speed (1G) operation using 62.5um/125um multimode graded index fiber optic cable
- Multiple FCR-302L-4 cards can operate simultaneously in a single chassis

Description

The FCR-302L-4 is a dual optical Fibre Channel receiver board for use in TTC's Airborne Instrumentation Multiplexer (AIM) products. The FCR-302L-4 provides two (2), receive only, optical Fibre Channel receivers that adhere to the open system Fibre Channel standards set and maintained by the American National Standards Institute (ANSI) Task Group X3T11. Each Fibre Channel receiver is capable of data rates of 1Gbps and data is captured on an external recorder. The Fibre Channel receiver pairs are accessible at the FCR-302L-4 faceplate via a 4 fiber optical D-Subminiature receptacle. One or more FCR-302L-4 cards can simultaneously reside in the AIM chassis. An OVH-350 overhead is required to transport data over gigabit Ethernet. The FCR-302L-4 driver and application software are available on the overhead card that resides in the same chassis as the FCR-302L-4.

Revision 05/11/2015

FCR-302L-4 Datasheet

©2015 Teletronics - A Curtiss-Wright Company
Specifications subject to change without notice.

Approved for Public Release 16-S-0013



CAIS
Compatible



Management
System
AS9100C
ISO 9001:2008

Teletronics - A Curtiss-Wright Company

15 Terry Drive, Newtown, PA 18940

phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com