

Airborne Instrumentation Multiplexer Overhead Card



Applications

- Distributed Systems
- CAIS Applications

Features

- Uses PowerPC microprocessor
- Contains: 128 MB DDR SDRAM and 32 MB FLASH memory
- Controls 66MHz, 64-bit PCI System Bus
- Has two serial ports to support system programming, to provide access to PCM Data via a “quick-look” function, gives access to health and maintenance data, time code status, and provides system wide Inventory Audit of all Remotes/Modules
- Has four General Purpose Inputs
- Has four General Purpose Outputs
- Accepts a mezzanine card (e.g., RCI-305) to provide Time Code functions as well as CAIS and IRIG-B interfaces

Description

The OVH-300A can accept a mezzanine card (e.g., RCI-305 CAIS and IRIG Interface Card). In addition to providing central processing and management, the OVH-300A includes several interfaces available on it’s front panel. These include RS-232/422 interfaces, four general-purpose, opto-coupled output signals and four general-purpose, LVTTTL input signals.

Revision 05/11/2015

OVH-300A Datasheet

©2015 Teletronics - A Curtiss-Wright Company
 Specifications subject to change without notice.

Approved for Public Release 16-S-1084

Teletronics - A Curtiss-Wright Company

15 Terry Drive, Newtown, PA 18940

phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com



CAIS
Compatible



Management
System
AS9100C
ISO 9001:2008