


10-Channel RTD Conditioner with Multiplexed Current Excitation



Applications

- Flight Test Instrumentation
- Factory Automation and Process Control
- Research Measurements and Experiments

Features

- 10-Channel RTD Conditioner Card
- Interfaces to 3 and 4 Wire RTD's
- Dual Tracking Constant Current Excitation per Card
- Compatible with the EDAU/CDAU/WDAU-20XX System
- > 10,000 Software Programmable Gains per Card
- $\pm 0.5\%$ System Accuracy
- Zero Calibration and Voltage Substitution
- 1,000 Megohms Input Impedance
- $\pm 35\text{VDC}$ Overvoltage Protection
- Programmed with Windows Based Software
- Windows 95/98/NT/2000 Software Included

Description

The RTD-110W is a 10-channel RTD signal conditioning card for use in TTC's EDAU/CDAU/WDAU-20XX series products. It is designed to interface to 3 and 4 wire RTDs. The module provides dual-tracking constant current excitation and signal conditioning for 3 and 4 wire RTD inputs. The excitation is multiplexed to each channel resulting in minimal transducer self-heating. The excitation level is programmable by the user. Provisions were made to allow the use of a single completion resistor (external-user selected). Each channel has programmable gain and offset capability. The conditioned analog signal is digitized at up to 12-bit resolution for transmission in the system PCM output format.

Revision 03/13/2009

RTD-110W Datasheet

©2009 Teletronics Technology Corporation
Specifications subject to change without notice.



Teletronics Technology Corporation
15 Terry Drive, Newtown, PA 18940
phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com