

2-Channel Serial PCM Input Card



Applications

- Integrate PCM encoders from different vendors
- Integrate low rate and high rate systems

Features

- 2-channel serial PCM multiplexer/encoder card
- Accepts two (2) IRIG-106-96 serial data streams
- FIFO based architecture
- Encodes data as an asynchronous embedded format
- Uses EMPTY flags to support data recovery
- Accepts NRZ-L/RNRZ-L data and bit clock
- RS-422 or TTL inputs
- Compatible with EDAU/CDAU-20XX product families
- Microsoft Windows application software included

Description

The SDI-102 is a 2-channel serial data input card for use in TTC's EDAU-20XX or CDAU-20XX series products. The card can be used to integrate PCM Encoders from different vendors with the TTC EDAU/CDAU product lines. Each channel accepts either single-ended or RS-422 differential inputs (data and clock) at standard rates up to 2 Mbps on a per-channel basis. All incoming data is FIFO buffered on the card and is selectable by the user for transmission in the PCM output format as Class I PCM (standard fixed-position). The embedded PCM data's format is not synchronized with the EDAU/CDAU PCM format.

Revision 02/21/2011

SDI-102 Datasheet

©2011 Teletronics Technology Corporation
Specifications subject to change without notice.



Teletronics Technology Corporation
15 Terry Drive, Newtown, PA 18940
phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com