

Miniature PCM to Network Gateway with IEEE 1588 Time



Applications

- Network-based data acquisition system
- Legacy PCM system to Network Data Acquisition System Gateway
- CAIS applications
- Airborne instrumentation system

Features

- Gateway between a PCM-based system and a networked data acquisition system
- Provides network capability to:
 - Configure the PCM system
 - Collect data from the PCM system
 - Timestamp the incoming PCM stream
- Acquires PCM clock and data from the PCM system
- Acquires time from the network in accordance with IEEE 1588
- Incorporates an RS-232/422 serial interface as a pass-through for setting up and configuring the PCM via the network
- Packetizes acquired data from the PCM and transports it over the network
- Built-in programmable frame correlator
- Supports simultaneous sampling capability
- SNMP MIB for statistics monitoring
- Environmentally sealed package
- Small installation footprint

Description

The Miniature PCM to Network Gateway (MnPCM-2000) provides a gateway between any generic PCM system and a network-based system. It provides a minor/major frame correlator, timestamps minor frames based on IEEE 1588 time, and packetizes data frames for transmission to the network. The unit also provides an RS-232/422 serial interface pass-through for setting up and configuring the PCM system. The unit supports Fast Ethernet (100BASE-T) that is fully compatible with IEEE 1588 to accept the grandmaster clock from the network.

Revision 09/21/2010

MnPCM-2000 Datasheet

©2010 Teletronics Technology Corporation
Specifications subject to change without notice.



Teletronics Technology Corporation
15 Terry Drive, Newtown, PA 18940
phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com