

Dual-Channel PCM Interface Module for MSSR-2010-SA & MSSR-110C Recorders



Applications

- Data Acquisition Systems
- Flight Test Data Recording
- Flight Test Instrumentation
- Lab Test

Features

- For use in TTC's MSSR-2010-SA and MSSR-110C Miniature IRIG-106 Chapter 10 Multiplexer/Recorder
- Two independent PCM Input Channels
- Channels supports RS-422 differential or single-ended TTL inputs
- Built-in programmable frame correlator for each input channel
- Operates up to 20Mbps per channel (RS-422 Differential inputs)
- Time tagging per IRIG Chapter 10
- 100% Data Recording
- Frame Lock output signals per channel
- Multiple MPCM-102M modules can be placed in a single recorder
- Configurable using TTC's Programmable Software Application

Description

The MPCM-102M-1 is a 2-channel, PCM Module for use in TTC's MSSR-2010-SA and MSSR-110C Miniature IRIG-106 Chapter 10 Multiplexer/Recorder. The module has two independent PCM channel inputs. Each channel accepts RS-422 differential inputs at rates up to 20Mbps on a per-channel basis. Both channels are also selectable to allow input on separate single-ended TTL input pins (5 Mbps maximum). The two PCM Data/Clock interfaces are accessible at the MPCM-102M faceplate via a single 37-Pin MDM connector. The total system bandwidth of all the input modules in a system should not exceed the maximum recorder bandwidth.

Revision 02/17/2009

MPCM-102M-1 Datasheet

©2009 Teletronics Technology Corporation
Specifications subject to change without notice.



Teletronics Technology Corporation
15 Terry Drive, Newtown, PA 18940
phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com