

Miniature Solid State Recorder with Removable CompactFlash Memory



Features

- Solid State PCM/Recorder
- Two Versions Available
 - Stand Alone with Internal Power Supply
 - MCDAU/MEDAU Stackable Utilizing the System Power Supply
- Ruggedized for Airborne Applications
- Uses up to 2 CompactFlash Cards
 - Up to 16 GB per Slot
 - Removable Data Transfer
- Acquires One PCM Input Channel
 - Data Rates up to 10 Mbps
 - Internal Frame Correlator
- Uses Digital Recording Format
 - Standard File Structure
 - Microsecond Frame Time Tag
 - Simplifies Direct Analysis from Media
 - PCM Regeneration Not Required
- Flexible Control/Status Interfaces
 - RS-232 (Setup/Control/Status)
 - Discrete (Control/Status)
- Compatible with MUX-300x products

Description

The MSSR solid state PCM Recorder is used in demanding applications such as airborne instrumentation recording. Two versions are available the MSSR-100C, a stackable version that works with TTC’s MCDAU and MEDAU encoders, and the MSSR-2000C-SA a stand alone version that includes an internal power supply. The unit is configured to handle one high speed serial PCM input at data rates up to 10 Mbps. A frame correlator decommutates the PCM data for direct file-structure recording. Plug-in CompactFlash cards are available with capacities up to 16 GB. The unit is programmable via serial RS-232. Control/Status is also provided. Acquired data can be analyzed/archived on a standard PC.

Applications

- Flight Test Instrumentation
- Limited Space Applications
- Portable Recording Systems
- Applications requiring Playback/Analysis on a standard laptop computer

Revision 02/09/2009

MSSR-2000C & MSSR-100C Datasheet

©2009 Teletronics Technology Corporation
 Specifications subject to change without notice.



Teletronics Technology Corporation
 15 Terry Drive, Newtown, PA 18940
 phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com