

Airborne Multimode Transmitter, High Efficiency



Features

- L & S Bands
- Multimode Modulator
- Supports: PCM/FM, SOQPSK, & Multi-H CPM
- Frequency Selectable via RS-232 COM Port
- Provides IRIG compatible Randomizer
- Data Rates
 - PCM/FM from 180 kbps to 20 Mbps
 - Others Formats from 360 kbps to 40 Mbps
- Bit Rate Agile
- High Efficiency Power Amplifier Design
- 2.0" x 3.0" x 1.0"
- Isolated Prime Power Supply
- Environmentally Rugged

Applications

- Missile Performance Testing
- Flight Test Instrumentation
- RPV Communications
- Space Craft Instrumentation
- Remote Ground Communication
- Home Security

Options

- IRIG Randomizer
- TTL or RS-422 Data interfaces
- RS-232/485 for Programming
- Internal Status for Temperature, Frequency
- Programmable Power Levels
- Custom Operating Frequency

Description

TTC's TTS-6500 series Multimode Transmitter provides the user with state-of-the-art modulation compatibility to IRIG-106-04, with user programmability for center frequency and modulation options with a high efficiency power amplifier chain. The TTS-6500 series provides an isolated prime power supply and the highest power efficiency offered in the industry today while being backed by outstanding customer support.

Revision 04/09/2009

TTS-6500 Series Datasheet

©2009 Teletronics Technology Corporation
 Specifications subject to change without notice.



Teletronics Technology Corporation
 15 Terry Drive, Newtown, PA 18940
 phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com