

Radar Enhancing C-Band Transponder



Features

- Miniature transponder
- RCC-262-02 compatible
- Solid state design
- C-band 5.4-5.9 GHz
- High efficiency isolated power supply
- Programmable via a serial COM port
 - Receiver and Transmitter Frequency
 - Pulse Width
 - Code Spacing
 - Reply Delay
- Sensitive superheterodyne receiver
- Crystal-controlled frequency stability
- Small form factor (14 cubic inches)
- Light weight (16 ounces)
- Mismatch protected from high antenna VSWR
- No pressurization required

Applications

- Instrumentation tracking radar
- Range expansion/enhancement
- UAVs, target drones, missiles & aircraft

Description

The XPDR-2150 series transponder from Teletronics Technology Corporation is the next generation of C-band transponders.

The units provide 50 watts of pulsed RF output and draw under 5 watts, giving this product line one of the lowest current draws in the industry today.

The XPDR-2150 is backward-compatible so that its form-factor matches legacy systems. There is no need to replace existing technology.

The transponder is programmable with the TTCWare configuration application or over a serial communications port using terminal emulation. An optional RS-485 multi-drop interface is also available.

Revision 10/21/2009

XPDR-2150 Datasheet

©2009 Teletronics Technology Corporation
Specifications subject to change without notice.



Teletronics Technology Corporation
15 Terry Drive, Newtown, PA 18940
phone: 267.352.2020 fax: 267.352.2021 Sales@ttcdas.com

www.ttcdas.com